



product details

L 36W/840 FLH1

Product description: L 36W/840 FLH1
 EAN/ Product: 4050300336763
 Quantity: Sleeves (FLH) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300336763

General Description	
Energy Label - EEI	A
Base (standard designation)	G13
Recycling	yes

Technical - Electrical Data	
Nominal wattage (packaging)	36 W

Technical - Geometries	
Tube diameter	26 mm
Length	1200 mm

Technical - Life	
Service life	18000 h ¹⁾
Lifespan	20000 h ²⁾

Technical - Light Technical Data	
Colour temperature	4000 K
Colour rendering group	1B
Colour rendering index Ra	80 ... 89
Light colour	840
Luminous flux	3350 lm ³⁾

Packaging units				
EAN	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300336763	Sleeves contains 1 Piece	40,000 mm x 29,000 mm x 1.260,000 mm	248,000 g (0,000 g)	1,315 Cubic dec.
4050300336770	Shipping carton box contains 10 Piece	177,000 mm x 60,000 mm x 1.287,000 mm	2.857,000 g (0,000 g)	13,668 Cubic dec.

system overview											
operation of lamp with	Length in mm	Number of lighting outlet	Length in mm	Width in mm	Height in mm	System power consumption in W (ECG)	System power consumption in W (CCG)	System power consumption in W (LLB)	Luminous flux with ECG in lumen	Luminous flux in lumen (CCG)	Power factor
HF 1x36/230-240 DIM	1200 mm	1	360 mm	30 mm	30 mm	36 W	46 W	44 W	3200 lm	3350 lm	0.96
QTP 1x36/230-240	1200 mm	1	360 mm	30 mm	30 mm	36 W	46 W	44 W	3200 lm	3350 lm	0.96
QT 1x36/230-240	1200 mm	1	237 mm	30 mm	30 mm	38 W	46 W	44 W	2900 lm	3350 lm	0.96
QT-ECO 1x36/230-240	1200 mm	1	150 mm	41 mm	28 mm	36 W	46 W	44 W	2900 lm	3350 lm	0.87
HF 2x36/230-240 DIM	1200 mm	2	423 mm	30 mm	30 mm	71 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QTP 2x36/230-240	1200 mm	2	423 mm	30 mm	30 mm	70 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QT 2x36/230-240	1200 mm	2	280 mm	42 mm	30 mm	71 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QTI 1x14/24/21/39	1200 mm	1	360 mm	30 mm	21 mm	36 W	46 W	44 W	3200 lm	3350 lm	0.96
QTI 2X14/24/21/39	1200 mm	2	423 mm	30 mm	21 mm	70 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96



product details

L 36W/840 FLH1

system overview											
operation of lamp with	Length in mm	Number of lighting outlet	Length in mm	Width in mm	Height in mm	System power consumption in W (ECG)	System power consumption in W (CCG)	System power consumption in W (LLB)	Luminous flux with ECG in lumen	Luminous flux in lumen (CCG)	Power factor
QTIS E 2x36/220-240	1200 mm	2	360 mm	30 mm	30 mm	71 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QTI DALI 1X36 DIM	1200 mm	1	360 mm	30 mm	21 mm	35 W	46 W	44 W	3200 lm	3350 lm	0.96
QTIS e 1x36/220-240	1200 mm	1	360 mm	30 mm	30 mm	36 W	46 W	44 W	3200 lm	3350 lm	0.96
QTI DALI 2X36 DIM	1200 mm	2	423 mm	30 mm	21 mm	70 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QTIS e 3x36/220-240	1200 mm	3	423 mm	40 mm	30 mm	71 W	95 W	89 W	2 * 3200 lm	2 * 3350 lm	0.96
QT-M 1X26-42/230-240	1200 mm	1	103 mm	67 mm	31 mm	35 W	46 W	44 W	3200 lm	3350 lm	0.96
QTP8 1X36	1200 mm										
QTP8 2X36	1200 mm										
QT8 1X36	1200 mm										
QT8 2X36	1200 mm										

1) with preheat ECG

2) with preheat ECG

3) At 25°C