

OliNo Energy BV

Operator Marcel van der Steen
 Telephone
 Fax
 e-Mail

Fledlight 001 Fledlight FL 20 x 20 opal high power / UGR-Table

Luminaire: Fledlight 001 Fledlight FL 20 x 20 opal high power
 Lamps: 36 x LED

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	19.7	21.0	20.0	21.3	21.5	19.7	21.0	20.0	21.3	21.5
	3H	21.5	22.7	21.8	23.0	23.3	21.5	22.7	21.8	23.0	23.3
	4H	22.2	23.3	22.5	23.6	23.9	22.2	23.3	22.5	23.6	23.9
	6H	22.6	23.7	23.0	24.0	24.3	22.6	23.7	23.0	24.0	24.3
	8H	22.8	23.8	23.1	24.1	24.4	22.7	23.8	23.1	24.1	24.4
	12H	22.8	23.8	23.2	24.1	24.5	22.8	23.8	23.2	24.1	24.4
4H	2H	20.3	21.4	20.6	21.7	22.0	20.3	21.4	20.6	21.7	22.0
	3H	22.3	23.3	22.7	23.6	24.0	22.3	23.3	22.7	23.6	24.0
	4H	23.1	24.0	23.5	24.3	24.7	23.1	24.0	23.5	24.3	24.7
	6H	23.7	24.5	24.1	24.8	25.2	23.7	24.4	24.1	24.8	25.2
	8H	23.9	24.6	24.3	25.0	25.4	23.9	24.6	24.3	25.0	25.4
	12H	24.0	24.6	24.4	25.0	25.4	24.0	24.6	24.4	25.0	25.4
8H	4H	23.4	24.1	23.8	24.5	24.9	23.4	24.1	23.8	24.5	24.9
	6H	24.1	24.7	24.6	25.1	25.6	24.1	24.7	24.6	25.1	25.6
	8H	24.4	24.9	24.9	25.3	25.8	24.4	24.9	24.9	25.3	25.8
	12H	24.5	24.9	25.0	25.4	25.9	24.5	24.9	25.0	25.4	25.9
12H	4H	23.4	24.1	23.9	24.5	24.9	23.4	24.1	23.9	24.5	24.9
	6H	24.2	24.7	24.7	25.1	25.6	24.2	24.7	24.7	25.1	25.6
	8H	24.5	24.9	25.0	25.4	25.9	24.5	24.9	25.0	25.4	25.9
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.1 / -0.1					+0.1 / -0.1				
S = 1.5H		+0.2 / -0.3					+0.2 / -0.3				
S = 2.0H		+0.4 / -0.6					+0.4 / -0.6				
Standard table		BK06					BK06				
Correction Summand		6.1					6.1				
Corrected Glare Indices referring to 1396lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 1.00.