

Operator
Telephone
Fax
e-Mail

LED's Light Pro 2400306 LED lijnarmatuur IP66 70W 8000lm 4000K / UGR-Table

Luminaire: LED's Light Pro 2400306 LED lijnarmatuur IP66 70W 8000lm 4000K
Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling	70	70	50	50	30	70	70	50	50	30	
ρ Walls	50	30	50	30	30	50	30	50	30	30	
ρ Floor	20	20	20	20	20	20	20	20	20	20	
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22.4	23.6	22.7	23.8	24.1	24.1	25.3	24.3	25.5	25.7
	3H	22.5	23.6	22.8	23.8	24.1	25.0	26.1	25.4	26.4	26.7
	4H	22.4	23.5	22.8	23.7	24.0	25.3	26.4	25.7	26.6	26.9
	6H	22.4	23.3	22.7	23.6	23.9	25.5	26.4	25.8	26.7	27.0
	8H	22.4	23.3	22.7	23.6	23.9	25.5	26.4	25.9	26.7	27.1
	12H	22.3	23.2	22.7	23.5	23.9	25.5	26.4	25.9	26.7	27.1
4H	2H	22.9	23.9	23.2	24.2	24.5	24.3	25.4	24.7	25.6	25.9
	3H	23.1	23.9	23.4	24.3	24.6	25.5	26.3	25.8	26.6	27.0
	4H	23.1	23.8	23.5	24.2	24.6	25.8	26.6	26.2	26.9	27.3
	6H	23.1	23.7	23.5	24.1	24.5	26.1	26.8	26.5	27.1	27.5
	8H	23.1	23.7	23.5	24.0	24.5	26.2	26.8	26.6	27.2	27.6
	12H	23.0	23.6	23.5	24.0	24.4	26.2	26.7	26.7	27.2	27.6
8H	4H	23.2	23.8	23.6	24.2	24.6	25.8	26.4	26.3	26.8	27.2
	6H	23.2	23.7	23.7	24.1	24.6	26.1	26.6	26.6	27.0	27.5
	8H	23.2	23.6	23.7	24.1	24.6	26.2	26.7	26.7	27.1	27.6
	12H	23.2	23.6	23.7	24.0	24.5	26.3	26.7	26.8	27.1	27.6
12H	4H	23.2	23.7	23.6	24.2	24.6	25.8	26.3	26.2	26.7	27.2
	6H	23.2	23.6	23.7	24.1	24.6	26.1	26.5	26.6	27.0	27.4
	8H	23.2	23.6	23.7	24.1	24.6	26.2	26.6	26.7	27.0	27.5
Variation of the observer position for the luminaire distances S											
S = 1.0H	+0.4 / -0.6					+0.2 / -0.3					
S = 1.5H	+1.3 / -2.7					+0.6 / -0.9					
S = 2.0H	+2.3 / -4.9					+1.1 / -1.6					
Standard table	BK01					BK03					
Correction Summand	5.1					8.5					
Corrected Glare Indices referring to 7650lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.