

Operator  
Telephone  
Fax  
e-Mail

## DMLUX Verlichtingsarmaturen DM720947-NT Triton LED Downlight 8W/840 767lm 105x55mm / UGR-Table

Luminaire: DMLUX Verlichtingsarmaturen DM720947-NT Triton LED Downlight 8W/840 767lm 105x55mm  
Lamps: 1 x LED

<b>Glare Evaluation According to UGR</b>											
$\rho$ Ceiling		70	70	50	50	30	70	70	50	50	30
$\rho$ Walls		50	30	50	30	30	50	30	50	30	30
$\rho$ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X      Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	24.4	25.3	24.6	25.5	25.7	24.4	25.3	24.6	25.5	25.7
	3H	24.9	25.7	25.2	26.0	26.2	24.9	25.7	25.2	26.0	26.2
	4H	25.0	25.9	25.4	26.1	26.4	25.0	25.9	25.4	26.1	26.4
	6H	25.1	25.9	25.5	26.2	26.5	25.1	25.9	25.5	26.2	26.5
	8H	25.2	25.9	25.5	26.2	26.5	25.2	25.9	25.5	26.2	26.5
	12H	25.2	25.8	25.5	26.2	26.5	25.2	25.8	25.5	26.2	26.5
4H	2H	24.6	25.4	24.9	25.6	25.9	24.6	25.4	24.9	25.6	25.9
	3H	25.2	25.9	25.6	26.2	26.5	25.2	25.9	25.6	26.2	26.5
	4H	25.5	26.1	25.9	26.4	26.8	25.5	26.1	25.9	26.4	26.8
	6H	25.7	26.2	26.1	26.6	26.9	25.7	26.2	26.1	26.6	26.9
	8H	25.7	26.2	26.1	26.6	27.0	25.7	26.2	26.1	26.6	27.0
	12H	25.7	26.2	26.2	26.6	27.0	25.7	26.2	26.2	26.6	27.0
8H	4H	25.6	26.0	26.0	26.4	26.8	25.6	26.0	26.0	26.4	26.8
	6H	25.8	26.2	26.3	26.6	27.1	25.8	26.2	26.3	26.6	27.1
	8H	25.9	26.2	26.4	26.7	27.1	25.9	26.2	26.4	26.7	27.1
	12H	25.9	26.2	26.4	26.7	27.2	25.9	26.2	26.4	26.7	27.2
12H	4H	25.6	26.0	26.0	26.4	26.8	25.6	26.0	26.0	26.4	26.8
	6H	25.8	26.1	26.3	26.6	27.0	25.8	26.1	26.3	26.6	27.0
	8H	25.9	26.2	26.4	26.6	27.1	25.9	26.2	26.4	26.6	27.1
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.6 / -0.9					+0.6 / -0.9				
S = 1.5H		+1.4 / -1.6					+1.4 / -1.6				
S = 2.0H		+2.6 / -2.3					+2.6 / -2.3				
Standard table		BK02					BK02				
Correction Summand		7.8					7.8				
Corrected Glare Indices referring to 767lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.