

**Lamp measurement report - 13 April 2016**

**ONT-02113-12x18**

by

**Triolight B.V.**



## Lamp measurement report - 13 April 2016

### Summary measurement data dated 2016-04-07

parameter	meas. result	remark
Color temperature	2782 K	warm white
Luminous intensity I <sub>v</sub>	46.2 Cd	Measured straight underneath the lamp.
Illuminance modulation index	0 %	Measured with a light sensor looking at the lamp (angle not defined). Is a measure for the amount of flickering.
Beam angle	136 deg	136 deg is the beam angle for the C0-C180-plane (perpendicular to the length direction of the lamp) and 113 deg is the beam angle for the C90-C270 plane, which is along the length direction of the lamp.
Power P	7.9 W	The net power consumed.
Power Factor	1.00	The tests were done with a DC power supply. This results in no blind power and as a result the power factor is always 1.0 but not relevant to mention.
THD	NaN %	Total Harmonic Distortion, is not present as a DC voltage was used to power the lamp so a DC current resulted which has no THD.
Luminous flux	172 lm	Measured with photogoniometer, calculation done as described in LM79-08.
Luminous efficacy	22 lm/W	Be aware that a DC power supply has been used. The found efficacy with this measurement is excluding the power supply that normally is needed to convert the grid voltage (230 V AC) to the used DC voltage. By excluding the consumption of the power supply the efficacy found here is higher than it would be when the power supply had been included.
EU2013-label classification	B	The energy class, from A++ (more efficient) to E (least efficient). This label is an update of the previous version, and compulsory from Sept 2013.
CRI_Ra	89	Color Rendering Index.
Qa_CQS	90.0	QCS (v9.0.3) is an improved indicator (over CRI) of how well colors are rendered.
Qg_CQS	0.96	Gamut Area Ratio.
Coordinates chromaticity diagram	x=0.3998 en y=0.4483	
Fitting	24V DC	
PAR-value	0.5 $\mu\text{Mol/s/m}^2$	The number of photons seen by an average plant when it is lit by the light of this light bulb. Value valid at 1 m distance from light bulb.

## Lamp measurement report - 13 April 2016


parameter	meas. result	remark
PAR-photon efficacy	0.2 uMol/s/W_e	The total emitted number of photons by this light, divided by its consumption in W. It indicates a kind of efficacy in generating photons.
Photon current	3.0 uMol/s	The total number of photons in the light of this lamp.
S/P ratio	1.4	This factor indicates the amount of times more efficient the light of this light bulb is perceived under scotopic circumstances (low environmental light level).
L x W x H external dimensions	1000 mm x 12 mm x 18 mm	External dimensions of the lamp.
L x W luminous area	1000 mm x 12 mm	Dimensions of the luminous area (used in Eulumdat file). It is the surface of the top of the light line.
General remarks		<p>The ambient temperature during the whole set of illuminance measurements was 26.7 - 27.9 deg C. The temperature of the lamp gets maximally about 21.5 degrees hotter than ambient temperature. Warm up effect: During the warmup time the illuminance varies during 28 minutes and decreases with 11 %.</p> <p>During the warmup time the power varies during 23 minutes and decreases with 8 %.</p> <p>The variation in efficacy (calculated as indication by simply dividing the illuminance by the power) during the warming up is -4 %. A very high negative value indicates a significant decrease for instance due to heating up of the lamp (decrease of lifetime). Voltage dependency: There is no (significant) dependency of the illuminance when the power voltage varies between 22 - 26 V DC.</p> <p>There is a constant dependency of the consumed power when the power voltage varies between 22 - 26 V DC. At the end of the article an additional photo.</p>
Eff-variation	-4 %	This is the variation in efficacy (calculated as indication by simply dividing the illuminance by the power) during the warming up. A very high negative value indicates a significant decrease for instance due to heating up of the lamp (decrease of lifetime).
Dimmable	yes	Info from manufacturer.
Melanopic effect factor	0.441	According to norm DIN SPEC 5031-100:2015-08.
Blue Light Hazard risk group	0	0=exempt, 1=low, 2 = moderate, 3=high risk.
form factor	bar	

## Lamp measurement report - 13 April 2016

parameter	meas. result	remark
article number	ONT-02113-12x18	

Note: one lamp has been measured on light output while more lamps were connected on the power supply (in this case 0.2 pieces). This to represent the most occurring situation. All power and current values of the total set are computed back to one lamp.

### Overview table

m.	Ø 50%		C0-180: 136° C90-270: 113°	E (lux)	Luminaire Efficacy	
	C0-180	C90-270			22 (lumen per Watt)	
5	24.5	15.1		2	Half-peak diam C0-180	
7.5	36.8	22.7		1	24.53 x diameter(m)	
10	49.1	30.3		0	Half-peak diam C90-270	
12.5	61.3	37.8		0	15.14 x diameter(m)	
15	73.6	45.4		0	Illuminance	
17.5	85.9	53		0	46 / distance <sup>2</sup> (lux)	
20	98.1	60.6		0	Total Output	
					172 (lumen)	

Please note that this overview table makes use of calculations, use this data with care as explained on the OLiNo site.

## Lamp measurement report - 13 April 2016

### EU 2013 Energy label classification


Since Sept 2013 these labels will be needed.

Important for the energy classification are the corrected rated power and the useful luminous flux.

The measured rated power is 7.9 W and might need to be corrected. The correction is dependent from the lamp type and whether or not the lamp control gear is included or not. The choice for this lamp is the following classification: **Lamps operating on external LED lamp control gear**. As a result the corrected rated power becomes: 8.7 W.


The luminous flux measured is 172 lm. The classification of this lamp needed to determine the useful flux is: **Non-directional lamps**. Then the useful flux becomes 172 lm. Now a reference power can be calculated.

The energy efficiency coefficient is  $P_{corr} / P_{ref} = 0.44$ .



EU energy label for this lamp

## Lamp measurement report - 13 April 2016




*The lamp's performance in the lumen-Watt field, with the energy efficacy fields indicated.*

## Lamp measurement report - 13 April 2016

### Eulumdat light diagram

This light diagram below comes from the program Qlumedit, that extracts these diagrams from an Eulumdat file.




*The light diagram giving the radiation pattern.*

The light diagram indicates the beam in the C0-C180 plane (perpendicular to the length direction of the lamp) and in the plane perpendicular to that, the C90-C270 plane (along the length direction of the lamp).

## Lamp measurement report - 13 April 2016

### Illuminance $E_v$ at 1 m distance, or luminous intensity $I_v$

Herewith the plot of the *averaged* luminous intensity  $I_v$  as a function of the inclination angle with the light bulb.




*The radiation pattern of the light bulb.*

This radiation pattern is the average of the light output of the light diagram given earlier. Also, in this graph the luminous intensity is given in Cd.

These averaged values are used (later) to compute the lumen output.



## Lamp measurement report - 13 April 2016



*Intensity data of every measured turn angle at each inclination angle.*

This plot shows per inclination angle the intensity measurement results for each turn angle at that inclination angle. There normally are differences in illuminance values for different turn angles. However for further calculations the averaged values will be used.

When using the average values per inclination angle, the beam angle can be computed, being 136 deg for the C0-C180 plane and 113 deg for the C90-C270 plane.

### Luminous flux

With the averaged illuminance data at 1 m distance, taken from the graph showing the averaged radiation pattern, it is possible to compute the luminous flux.

The result of this computation for this light spot is a luminous flux of 172 lm.

### Luminous efficacy

The luminous flux being 172 lm, and the consumed power of the lamp being 7.9 Watt, results in a luminous efficacy of 22 lm/Watt.


## Lamp measurement report - 13 April 2016

### Electrical properties


The power factor is 1.00. The tests were done with a DC power supply. This results in no blind power and as a result the power factor is always 1.0 but not relevant to mention.

Lamp voltage	23.96 V
Lamp current	0.331 A
Power P	7.9 W
Apparent power S	7.9 VA
Power factor	1.00

### Temperature measurements lamp



## Lamp measurement report - 13 April 2016




Temperature image(s).

status lamp	> 2 hours on
ambient temperature	26.9 deg C
reflected background temperature	26.9 deg C
camera	Flir T335
emissivity	0.95
measurement distance	0.3, 0.7 m
IFOV_geometric	0.136 mm per 0.1 m distance
NETD (thermal sensitivity)	50 mK

## Lamp measurement report - 13 April 2016

### Color temperature and Spectral power distribution




*The spectral power distribution of this light bulb, energies on y-axis valid at 1 m distance.*

The measured color temperature is 2782 K which is warm white.

This color temperature is measured straight underneath the light bulb. Below a graph showing the color temperature for different inclination angles.

## Lamp measurement report - 13 April 2016



*Color temperature as a function of inclination angle.*

The color temperature is given for inclination angles up to 85 deg. Beyond that value the illuminance is so low ( $< 0.10$  lux) that it has not been used for color determination of the light.


For the C0-C180 plane: the beam angle of 136 deg is equivalent to 67.8 deg inclination angle, which is the area where most of the light falls within. The maximum variation of color temperature in this inclination area is about 1 %.

For the C90-C270 plane: the beam angle of 113 deg is equivalent to 56.6 deg inclination angle, which is the area where most of the light falls within. The maximum variation of color temperature in this inclination area is about 3 %.

## Lamp measurement report - 13 April 2016

### PAR value and PAR spectrum

To make a statement how well the light of this light bulb is for growing plants, the PAR-area needs to be determined.




The photon spectrum, then the sensitivity curve and as result the final PAR spectrum of the light of this light bulb

parameter	value	unit
PAR number	0.5	uMol/s/m <sup>2</sup>
PAR photon current	1.8	uMol/s
PAR photon efficacy	0.2	uMol/s/W

The PAR efficiency is 65 % (valid for the PAR wave length range of 400 - 700 nm). This is the maximum percentage of the total of photons in the light that is effectively used by the average plant (since the plant might not take 100 % of the photons at the frequency where its relative sensitivity is 100 %).

## Lamp measurement report - 13 April 2016

### S/P ratio




The power spectrum, sensitivity curves and resulting scotopic and photopic spectra (spectra energy content defined at 1 m distance).

The S/P ratio of the light coming from this lamp is 1.4.

## Lamp measurement report - 13 April 2016

### Chromaticity diagram



*The chromaticity space and the position of the lamp's color coordinates in it.*

The point of the light in this diagram is inside the area indicated with class B. This area indicates an area for signal lamps.

The color coordinates are  $x=0.3998$  and  $y=0.4483$ .




## Lamp measurement report - 13 April 2016

### Color Rendering Index (CRI) or also Ra

Herewith the image showing the CRI as well as how well different colors are represented (rendered). The higher the number, the better the resemblance with the color when a black body radiator would have been used (the sun, or an incandescent lamp)

Each color has an index  $R_x$ , and the first 8 indexes ( $R_1 \dots R_8$ ) are averaged to compute the  $R_a$  which is equivalent to the CRI.



*CRI of the light of this lightbulb.*

This value of 89 indicates how well the light of this lamp can render well a set of reference colors, this in comparison with the light of a reference source (for color temperatures  $< 5000\text{K}$  a black radiator is used as reference and for color temperatures  $> 5000\text{K}$  the sun or the light outside during the day).

The value of 89 is bigger than the value of 80 that is considered as a minimum for working areas in general.


Note: the chromaticity difference is  $-0.0030$  and indicates the distance to the Planckian Locus. There is a value mentioned of max  $5.4\text{E-}3$  in section 5.3 of CIE 13.3-1995 however not further explanation of it.

An other reference with signal lights as a reference is given in the chromaticity diagram.


## Lamp measurement report - 13 April 2016

### Color Quality Scale

(v9.0.3) is an improved indicator (over CRI) of how well colors are rendered.



CQS-values of the light of this light bulb.




CQS-values for the light of this light bulb compared with those of a reference source with the same color temperature.

## Lamp measurement report - 13 April 2016

### Voltage dependency

The dependency of a number of lamp parameters on the lamp voltage is determined. For this, the lamp voltage has been varied and its effect on the following light bulb parameters measured: illuminance  $E_v$  [lx], the lamp power  $P$  [W] and the luminous efficacy [lm/W] (this latter is estimated here by dividing the found  $E_v$  value by  $P$ ).



*Lamp voltage dependencies of certain light bulb parameters*

There is no (significant) dependency of the illuminance when the power voltage varies between 22 - 26 V DC.



There is a constant dependency of the consumed power when the power voltage varies between 22 - 26 V DC.

When the voltage varies abruptly with + or - 0.5 V DC then this results in a variation of the illuminance of maximally 0.0 %. This difference in illuminance is not visible (when it occurs abruptly).

## Lamp measurement report - 13 April 2016

### Warm up effects

After switch on of a cold lamp, the effect of heating up of the lamp is measured on illuminance  $E_v$  [lx], the lamp power  $P$  [W] and the luminous efficacy [lm/W].




Effect of warming up on different light bulb parameters. In the first graph the 100 % level is put at begin, and in the last graph the 100 % level is put at the end.

## Lamp measurement report - 13 April 2016

During the warmup time the illuminance varies during 28 minutes and decreases with 11 %. During the warmup time the power varies during 23 minutes and decreases with 8 %. The variation in efficacy (calculated as indication by simply dividing the illuminance by the power) during the warming up is -4 %. A very high negative value indicates a significant decrease for instance due to heating up of the lamp (decrease of lifetime).

### Measure of flickering

An analysis is done on the measure of flickering of the light output by this light bulb.



*The measure of fast illuminance variation of the light of the light bulb*

parameter	value	unit
Flicker frequency	1433.5	Hz
Illuminance modulation index	0	%
Flicker index	0.000	[-]

The illuminance modulation index is computed as:  $(\max_{Ev} - \min_{Ev}) / (\max_{Ev} + \min_{Ev})$ .

## Lamp measurement report - 13 April 2016

### Melanopic effect


The melanopic effect shows the level of impact the light of this lamp can have on the day-night rhythm of human beings (as well as the suppression of melatonin production). The important parameters (according to norm DIN SPEC 5031-100:2015-08):

melanopic effect factor	0.441
k_mel trans (25 years)	1.043
k_mel trans (32 years)	1.000
k_mel trans (50 years)	0.859
k_mel trans(75 years)	0.636
k_mel trans(90 years)	0.510
k_pupil(25 years)	1.088
k_pupil(32 years)	1.000
k_pupil(50 years)	0.792
k_pupil(75 years)	0.543
k_pupil(90 years)	0.416

## Lamp measurement report - 13 April 2016

### Blue Light Hazard

The amount of blue light and the harm it can cause on the retina has been determined. Herewith the results.



The level of blue light of this lamp related to the exposure limit and the different classification areas.

L_lum0 [mm]	12	Dimension of brightest part of lamp in C0-C180 direction.
L_lum90 [mm]	1000	Dimension of brightest part of lamp in C90-C270 direction.
SSD_500lx [mm]	304	Calculated distance where $E_v = 500$ lux. This computation is valid when it is in the far field of the lamp. Note: if this value 200 mm then the distance of 200 mm is taken as proposed in the norm IEC 62471:2006.
Start of far field [mm]	5000	Minimum distance at which the lamp can be seen as a point source. In this area the $E_v$ is linearly dependent from $(1/\text{distance})^2$ .
300-350 nm values stuffed with 0s	yes	In the event OliNo has measured with a SpB1211 spectrometer without UV option then the irradiance data of 300-349 nm is missing. For lamps where there is already no energy content near 350 nm, the values 300-349 can also be set at zero then.
alpha_C0-C180 [rad]	0.039	(Apparent) source angle in C0-C180 direction.
alpha_C90-C270 [rad]	3.289	(Apparent) source angle in C90-C270 direction.

## Lamp measurement report - 13 April 2016

alpha_AVG [rad]	0.070	Average (apparent) source angle. If average $\geq 0.011$ rad then the exposure limit is computed with radiance $L_b$ . Otherwise with irradiance $E_b$ .
Exposure value [ $W/m^2/sr$ ]	1.20E+0	Blue Light Hazard value for this lamp, measured straight underneath the lamp. Computation is referenced to $L_b$ . Because the distance at 500 lux is in the near field, then this exposure value is too pessimistic and should be lower.
Blue Light Hazard risk group	0	0=exempt, 1=low, 2 = moderate, 3=high risk.

### Extra



*Additional photos.*

#### Disclaimer

The information in this OliNo report is created with the utmost care. Despite this, the information could contain inaccuracies. OliNo cannot be held liable in this instance nor can the data in this report be legally binding.

We strive to adhere to all of the conditions of any copyright holder in the publication of any illustration/article or item. In the event that we unintentionally violate said copyright holder's conditions in our articles, we kindly ask to be contacted here at OliNo so that we can resolve any disputes, issues or misunderstandings.

#### License

It is permitted ONLY to use or publish this report in its entirety and in unaltered form via internet or other digital or written media in any form. To guarantee the reliability and accuracy of the report, it is strictly prohibited to change or alter parts of the report and/or republish it in a modified content.