

## Lamp measurement report – 10 Feb 2010

### Tube Led Light 150 cm

by  
Loko



## Lamp measurement report – 10 Feb 2010

### Summary measurement data

parameter	meas. result	remark
Color temperature	4461 K	Neutral white
Luminous intensity $I_v$	723 Cd	Measured straight underneath the lamp
Beam angle	110 deg	110° for the C0-C180 plane (crosses the length direction of the tube), and 107° for C90-C270 plane (along the length direction of tube).
Power P	24.1 W	Follow the link for more electrical and temperature properties.
Power Factor	0.92	For every 1 kWh net power consumed, there has been 0.4 kVAh for reactive power.
Luminous flux	2028 Lm	
Luminous efficacy	84 Lm/W	
CRI_Ra	70	Color Rendering Index.
Coordinates chromaticity diagram	x=0.3645 and y=0.3760	
Fitting	FL-tube	This tube is connected directly to the 230 V grid.
PAR-value	5.9 $\mu\text{Mol/s/m}^2$	The number of photons seen by an average plant when it is lit by the light of this light bulb. Value valid at 1 m distance from light bulb.
PAR-photon efficacy	0.7 $\mu\text{Mol/s/W}_e$	The total emitted number of photons by this light, divided by its consumption in W. It indicates a kind of efficacy in generating photons.
S/P ratio	1.6	This factor indicates the amount of times more efficient the light of this light bulb is perceived under scotopic circumstances (low environmental light level).




## Lamp measurement report – 10 Feb 2010

D x L external dimensions	29 x 1496 mm	External dimensions of the lamp (D = diameter, L = Length without pins).
L x W luminous area	1474 x 24 mm	Dimensions of the luminous area (used in Eulumdat file). This is equal to the surface of area on which the leds are mounted.
General remarks		<p>The ambient temperature during the whole set of measurements was 22-24.5 deg C. The maximum temperature of the tube light gets about 21 degrees hotter than ambient.</p> <p>Warm up effect: during the warm up time the illuminance decreases with 9 % and the consumed power with 3 %.</p> <p>Voltage dependency: the power consumption and illuminance do not significantly depend on the voltage when it is varied from 200 - 250 V.</p>

## Lamp measurement report – 10 Feb 2010


### Overview table

m.	Ø 50%		CO-180: 110° C90-270: 107°	E (lux)	Luminaire Efficacy
	CO-180	C90-270			84 (lumens per Watt)
0.25	0.71	0.68		11566	Half-peak diam CO-180
0.5	1.43	1.36		2891	2.86 x diameter(m)
1	2.86	2.71		723	Half-peak diam C90-270
1.5	4.28	4.07		321	2.71 x diameter(m)
3	8.57	8.14		80	Illuminance
4	11.43	10.86		45	723 / distance <sup>2</sup> (lux)
5	14.28	13.57		29	Total Output
					2028 (lumens)

The overview table is explained on the OLiNo website. Please note that this overview table makes use of calculations, use this data with care as explained on the OLiNo site. E (lux) values are not accurate, when within 5 x 1474 mm ≈ 7400 mm. Within this distance from the lamp, the measured lux values will be less than the computed values in this overview as the measurements are then within the near field of the lamp.

### Eulumdat light diagram

This light diagram below comes from the program Qlumedit, that extracts these diagrams from an Eulumdat file. It is explained on the OLiNo site.




## Lamp measurement report – 10 Feb 2010

*The light diagram giving the radiation pattern.*

It indicates the luminous intensity around the light bulb. The direction C90-C270 has a beam comparable to that of the C0-C180 plane.

### Illuminance $E_v$ at 1 m distance, or luminous intensity $I_v$

Herewith the plot of the *averaged* luminous intensity  $I_v$  as a function of the inclination angle with the light bulb.




*The radiation pattern of the light bulb.*

This radiation pattern is the average of the light output of the light diagram given earlier. Also, in this graph the luminous intensity is given in Cd.

These averaged values are used (later) to compute the lumen output.

## Lamp measurement report – 10 Feb 2010



*Intensity data of every measured turn angle at each inclination angle.*

This plot shows per inclination angle the intensity measurement results for each turn angle at that inclination angle. There normally are differences in illuminance values for different turn angles. However for further calculations the averaged values will be used. When using the average values per inclination angle, the beam angle can be computed, being  $110^\circ$  for the C0-C180 plane (crossing the length direction) and  $117^\circ$  in the C90-C270 plane (along the length direction).

### Luminous flux

With the averaged illuminance data at 1 m distance, taken from the graph showing the averaged radiation pattern, it is possible to compute the luminous flux.

The result of this computation for this light spot is a luminous flux of 2028 Lm.

### Luminous efficacy

The luminous flux being 2028 Lm, and the power of the light bulb being 24.1 W, yields a luminous efficacy of 84 Lm/W.


## Lamp measurement report – 10 Feb 2010

### Electrical properties

A power factor of 0.92 means that for every 1 kWh net power consumed, a reactive component of 0.4 kVAr was needed.

Lamp voltage	230 VAC
Lamp current	114 mA
Power P	24.1 W
Apparent power S	26.2 VA
Power factor	0.92


Of this light bulb the voltage across and the resulting current through it are measured and graphed. See the OLiNo site how this is obtained.



*Voltage across and current through the lightbulb*

This waveforms have been checked on requirements posed by the norm IEC 61000-3-2:2006 (including up to A2:2009). See also the explanation on the OLiNo website.

## Lamp measurement report – 10 Feb 2010



*Harmonics in in the current waveform and checked against IEC61000-3-2:2006*


There are no limits for the harmonics for led lighting equipment  $\leq 25$  W.

The Total Harmonic Distortion of the current is computed as 20 %.





## Lamp measurement report – 10 Feb 2010

### Temperature measurements lamp



Overview, look for the hotspots



The warmest position on the metal heat sink, measured on a piece of masking tape




## Lamp measurement report – 10 Feb 2010

status lamp	> 2 hours on
ambient temperature	24 deg C
reflected background temperature	24 deg C
camera	Flir BCAM
emissivity	0.95 <sup>(1)</sup>
measurement distance	0.10 m (closest zoom)
IFOV <sub>geometric</sub>	0.4 mm
NETD (thermal sensitivity)	100 mK

<sup>(1)</sup> The emissivity of the masking tape is used which is about 0.95. The masking tape is so thin that it quickly takes the same temperature as the light bulb's heat sink. The tube on its hottest side gets a bit hotter than warm-to-the-touch, being 45 deg C.

## Color temperature and Spectral power distribution




The spectral power distribution of this light bulb, energies on y-axis valid at 1 m distance.

The measured color temperature is about 4450 K which is neutral white.

This color temperature is measured straight underneath the light bulb. Below a graph

## Lamp measurement report – 10 Feb 2010

showing the color temperature for different inclination angles.



*Color temperature as a function of inclination angle.*


The measurement of CCT is measured for inclination angles up to 75° since then the illuminance value was decreased to very low values (< 5 lux).

The beam angle for the C0-C180 is 110°, meaning a 55° inclination angle. In this area the majority of the light is present. The variation in correlated color temperature in this area is ≈ 4 %.

## Lamp measurement report – 10 Feb 2010

### PAR value and PAR spectrum

To make a statement how well the light of this light bulb is for growing plants, the PAR-area needs to be determined. See the OLiNo website how this all is determined and the explanation of the graph.



*The photon spectrum, then the sensitivity curve and as result the final PAR spectrum of the light of this light bulb*


parameter	value	unit
PAR-number	5.9	$\mu\text{Mol/s/m}^2$
PAR-photon current	16.5	$\mu\text{Mol/s}$
PAR-photon efficacy	0.7	$\mu\text{Mol/s/W}$

The PAR efficiency is 63 % (valid for the PAR wave length range of 400 - 700 nm). So maximally 63 % of the total of photons in the light is effectively used by the average plant (since the plant might not take 100 % of the photons at the frequency where its relative sensitivity is 100 %).

## Lamp measurement report – 10 Feb 2010

### S/P ratio

The S/P ratio and measurement is explained on the OliNo website. Here the results are given.




*The power spectrum, sensitivity curves and resulting scotopic and photopic spectra (spectra energy content defined at 1 m distance).*

The S/P ratio is 1.6.

More info on S/P ratio can be found on the OliNo website.

## Lamp measurement report – 10 Feb 2010

### Chromaticity diagram



*The chromaticity space and the position of the lamp's color coordinates in it.*

The light coming from this lamp is close at the Planckian Locus (the black path in the graph).

Its coordinates are  $x=0.2645$  and  $y=0.3760$ .

## Lamp measurement report – 10 Feb 2010

### Color Rendering Index (CRI) or also Ra

Herewith the image showing the CRI as well as how well different colors are represented (rendered). The higher the number, the better the resemblance with the color when a black body radiator would have been used (the sun, or an incandescent lamp). Practical information and also some critics about the CRI can be found on the OliNo website. Each color has an index  $R_x$ , and the first 8 indexes ( $R_1 \dots R_8$ ) are averaged to compute the  $R_a$  which is equivalent to the CRI.

☐ manual

Reference Illuminant: Planckian radiator CCT: 4461 K

Chromaticity Difference DC= 4.7E-3

R1= 65.2	R8= 50.4	<b>R<sub>a</sub></b> (mean value of R1 - R8) <b>69.7</b>
R2= 76.8	R9= -42.1	
R3= 85.1	R10= 44.4	
R4= 67.3	R11= 60.8	
R5= 65.1	R12= 34.4	
R6= 66.4	R13= 67.2	
R7= 81.5	R14= 91.6	

*CRI of the light of this lightbulb.*


The value of 70 is lower than 80 which is considered a minimum value for indoor usage. Note: the chromaticity difference is 0.0047 indicates the distance to the Planckian Locus. There is no norm yet that states what the max deviation from white light is allowed to be.

### Voltage dependency

The dependency of a number of lamp parameters on the lamp voltage is determined. For this, the lamp voltage has been varied and its effect on the following light bulb parameters measured: illuminance  $E_v$  [lx], the lamp power  $P$  [W], the (Correlated) Color Temperature [K] and the luminous efficacy [lm/W].



## Lamp measurement report – 10 Feb 2010



Lamp voltage dependencies of certain light bulb parameters, where the value at 230 V is taken as 100 %.

The illuminance and consumed power do not (significantly) vary when the voltage is varied, in a linear matter.


When the voltage at 230 V varies with + and - 5 V, then the illuminance varies < 0.1 %, so when abrupt voltage changes occur this effect is not visible in the illuminance output.

### Warm up effects

After switch on of a cold lamp, the effect of heating up of the lamp is measured on illuminance E<sub>v</sub> [lx], color temperature CT or correlated color temperature CCT [K], the lamp power P [W] and the luminous efficacy [lm/W].



## Lamp measurement report – 10 Feb 2010



Effect of warming up on different light bulb parameters. At top the 100 % level is put at begin, and at bottom at the end.



## **Lamp measurement report – 10 Feb 2010**

The warm up time is about 30 minutes. During that time the illuminance decreases 9 % and the consumed power with 3 %.

### **Disclaimer**

The information in this OliNo report is created with the utmost care. Despite of this the information can have inaccuracies. OliNo cannot be held liable for the content of the information in this report nor for the consequences of its use. The data in this report is not legally binding.