

Operator
Telephone
Fax
e-Mail

Triolight liniLED Aeris Profile L30 Cover L30 4000K Photon 3000 / UGR-Table

Luminaire: Triolight liniLED Aeris Profile L30 Cover L30 4000K Photon 3000

Lamps: 1 x LED

Glare Evaluation According to UGR											
ρ Ceiling		70	70	50	50	30	70	70	50	50	30
ρ Walls		50	30	50	30	30	50	30	50	30	30
ρ Floor		20	20	20	20	20	20	20	20	20	20
Room Size X Y		Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
2H	2H	22.5	23.9	22.8	24.1	24.3	22.6	24.0	22.9	24.2	24.4
	3H	24.1	25.3	24.4	25.6	25.9	24.2	25.4	24.5	25.7	26.0
	4H	24.7	25.9	25.1	26.1	26.4	24.8	26.0	25.2	26.3	26.6
	6H	25.2	26.2	25.5	26.5	26.8	25.3	26.3	25.6	26.6	27.0
	8H	25.3	26.3	25.7	26.7	27.0	25.4	26.4	25.8	26.7	27.1
	12H	25.4	26.4	25.8	26.7	27.1	25.5	26.5	25.9	26.8	27.1
4H	2H	23.2	24.4	23.6	24.7	25.0	23.3	24.5	23.7	24.7	25.0
	3H	25.0	26.0	25.4	26.3	26.6	25.1	26.1	25.5	26.4	26.7
	4H	25.7	26.6	26.1	27.0	27.3	25.8	26.7	26.2	27.1	27.4
	6H	26.3	27.1	26.7	27.4	27.8	26.4	27.2	26.8	27.5	27.9
	8H	26.5	27.2	26.9	27.6	28.0	26.6	27.3	27.0	27.7	28.1
	12H	26.7	27.3	27.1	27.7	28.1	26.7	27.3	27.2	27.8	28.2
8H	4H	26.1	26.7	26.5	27.1	27.6	26.1	26.8	26.6	27.2	27.6
	6H	26.8	27.3	27.2	27.8	28.2	26.8	27.4	27.3	27.8	28.3
	8H	27.0	27.5	27.5	28.0	28.5	27.1	27.6	27.6	28.0	28.5
	12H	27.2	27.7	27.7	28.1	28.6	27.3	27.7	27.8	28.2	28.7
12H	4H	26.1	26.7	26.5	27.1	27.5	26.2	26.8	26.6	27.2	27.6
	6H	26.8	27.3	27.3	27.8	28.2	26.9	27.4	27.4	27.8	28.3
	8H	27.1	27.6	27.6	28.0	28.5	27.2	27.6	27.7	28.1	28.6
Variation of the observer position for the luminaire distances S											
S = 1.0H		+0.1 / -0.1					+0.1 / -0.1				
S = 1.5H		+0.2 / -0.3					+0.2 / -0.3				
S = 2.0H		+0.4 / -0.7					+0.4 / -0.6				
Standard table		BK06					BK06				
Correction Summand		9.9					9.9				
Corrected Glare Indices referring to 1693lm Total Luminous Flux											

The UGR values have been calculated according to CIE Publ. 117 Spacing-to-Height-Ratio = 0.25.